

**FEATURES**

- Reliable illumination - requiring no additional electricity to operate
- Constant, uniform illumination - visible at 50 feet in total blackout or heavy smoke conditions
- Ultra-compact, low-profile design
- Designed for both high- or low-level installations
- Non-toxic, non-radioactive materials
- Low cost - easy installation
- Requires virtually no maintenance with periodic inspections for over 25 years
- Available in ceiling, back or end mount
- Available in framed and unframed faces with colors: red, green, or white

**CONFORMANCE TO CODES AND STANDARDS**

Conforms to IEC ES #6040 meeting all current building codes: 1997 Uniform Building Code™, the 2000 International Building Code®, the BOCA® National Building Code/1999 and the 1999 Standard Building Code®. Meets NFPA Life Safety Code 101® and 101B®, NFPA 5000 Building Construction & Safety Code™, 1998 California Building Code, 1998 California Fire Code, 2003 International Building Code® and OSHA.

Model: \_\_\_\_\_ Date: \_\_\_\_\_  
 Accessories: \_\_\_\_\_  
 Job Name: \_\_\_\_\_ Type: \_\_\_\_\_

**While Supplies Last**  
*(Limited Configurations Available, See Below)*



**ORDERING INFORMATION Example: PL-1-F-1-R**

SKU	Description	Accessories (Field Installed, Order as Separate Line Item)
PL-1-F-2-G	Single Face Sign, Framed, Green Finish, w/ Mounting Bracket	WG-1 = Wire Guard (Back Mount)
PL-1-F-1-R	Single Face Sign, Framed, Red Finish, Wall Mount	WG-2 = Wire Guard (End Mount)
PL-1-F-1-W	Single Face Sign, Framed, White Finish, Wall Mount	WG-3 = Wire Guard (Ceiling Mount)
PL-MB-G	Mounting Bracket, Green	XG-6 = Poly Guard (Back Mount)
PL-MB-W	Mounting Bracket, White	

## TECHNICAL INFORMATION

Sizes:	8.25" x 15.25" x .25" (Sortie 8" x 22.1875" x .25")
Letter size:	.875" stroke with 7" height
Background:	Red, Green or White
Illumination:	High Visibility Green
Visibility:	PL = 50 feet
Directional:	Pop-out chevron arrows for easy direction selection
Construction:	.035 steel and a plastic photoluminescent panel
Durability:	Explosion-proof for areas requiring explosion-proof exit signage
Tests Passed:	Conforms to ICC ES #6040, CA State Fire Marshall Listing #6200-1617; 100; City of Los Angeles Research Report: RR 25531 (CSI #16530) Ontario Building Material Evaluation Commission Authorization Report BMEC #03-12-291
Life Expectancy:	25+ years
Power Requirements:	No additional electrical or mechanical source required
Installation:	For indoor use only. Do not expose to direct sunlight, liquid spray or temperatures outside the rated range of 50°F to 104°F (10°C to 40°C).  Surface, flag or ceiling mounted (hardware included). Before installation it must be determined that there is a minimum of 54 lux of ambient fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during occupancy.
Applications:	Both high-level and low-level

## CONSTRUCTION

The PL series of exits are constructed of .035 steel housing with a plastic photoluminescent panel with Field-selectable chevrons for easy direction selection.

## ILLUMINATION

Fully illuminated 7" letters with .875" stroke is achieved utilizing engineered photoluminescent panel. Green letters are visible at 50'

## INSTALLATION

Surface, flag or ceiling mounted (hardware included). Before installation it must be determined that there is a minimum of 54 lux of ambient fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during occupancy.

Ideal for explosion-proof areas or other applications where a direct power source is not available for high-level or low-level installations.

## CONFORMANCE TO CODES & STANDARDS

The PL Series meets or exceeds the following: UL 924, NEC requirements and NFPA 101.



Flag Mount Option



Ceiling Mount Option