

Exitronix Self Luminous Signs are the practical solution for exit and safety signs where electricity is unavailable. These signs are totally self-contained, durable and attractive. They are completely free of outside energy sources and provide 10 to 20 years of continuous, maintenance-free illumination.

The Institutional Frame (IF) option turns this fixture into a rugged, institutional exit sign that provides dependable illumination in the most demanding applications. The 3/8" thick polycarbonate facing and rugged steel angled frame deter vandalism and abuse.

FEATURES

- Energy efficient, consumes zero electricity during effective life of 10 or 20 years
- Explosion-proof, contains no electrical components or spark producing matter, ideal for hazardous location applications
- Maintenance-free unit, contains no circuitry, lamps or batteries to replace
- Self-powered, always illuminated. Sign provides constant, uninterrupted illumination and requires no external power source
- Extreme temperature rated; unit is rated to operate in temperatures from -76°F to 212°F (-60°C to 100°C)
- Custom legends available
- Designed for both high- or low-level installations
- Ceiling, wall or end mount
- Vibration-proof
- Optional security lens available
- Available with face colors red, green, black or white
- Available with frame colors gray, black or white
- Single or double face configurations
- Fully-illuminated 6" characters with 3/4" stroke
- Suitable for wet location
- Assembled in U.S.A.

WARRANTY

Our PXP series is warranted against any defects in material or workmanship for the rated life of the product.

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



PXP-1R-20-BL



Institutional Frame Option (IF)



ORDERING INFORMATION Example: PXP-1B-20-WH

Series	No. of Faces/Color	Product Life	Frame Finish	Options (Factory Installed)	Accessories ³ (Field Installed)
PXP	1B = Single Face Black	10 = 10 Years	WH = White	IF ¹ = Institutional Frame	WG-1 = Wire Guard (Back Mount)
	2B = Double Face Black	20 = 20 Years	BL = Black	SL ² = Security Polycarbonate Lens	WG-2 = Wire Guard (End Mount)
	1G = Single Face Green		BA = Brushed Aluminum	SS = Custom Legend	WG-3 = Wire Guard (Ceiling Mount)
	2G = Double Face Green		GR = Gray	PM = 12" Pendant	XG-6 = Poly Guard (Back Mount)
	1R = Single Face Red				
	2R = Double Face Red				
	1W = Single Face White				
	2W = Double Face White				

Notes

- ¹ Single face only, not available with BA or GR finish
- ² Not available with BA finish
- ³ Order as separate line item

CONSTRUCTION

Frame

Constructed of flame retardant ABS Plastic

ILLUMINATION

Fully illuminated 6" letters with 3/4" stroke is achieved with a safe light source that consists of sealed glass tubes, internally coated with phosphor and filled with tritium gas. This process provides a completely self-contained, highly durable and attractive means of illumination without the affects of power outages or brown-outs. Minimum initial illumination at time of manufacture is 0.15 foot lamberts. PXP has a 100' visibility rating.

INSTALLATION

PXP

Snap-together design allows for quick, easy installation. Universal mounting bracket supplied.

Return/Disposal

Exitronix will accept returns for proper disposal – contact factory for details and shipping documents. It is unlawful to abandon or dispose of self-luminous signs except by transfer to persons specifically licensed by the Nuclear Regulatory Agency or by an Agreement State. Exitronix reserves the right to charge for disposal.

Wet Location Rated

Wet location rated fixtures can be used in applications where moderate contact with water can be expected. Wet-location rated products are designed to be reasonably watertight; they require a seal around the base, canopy, or bracket to protect the electrical service from moisture.

Assembled in the U.S.A. (Standard)

Manufactured in the U.S.A. and is in full compliance with the American Recovery and Reinvestment Act of 2009 (ARRA) requirements and Buy American provisions.

Institutional Frame "IF"

Single Face - Attractive, vandal resistant 13 gauge cold rolled steel construction with solid 3/8" thick polycarbonate lens.

Security Lens (Option: SL)

Providing a security lens to exit fixtures offers additional protection to the unit against intentional or unintentional abuse. Constructed of 3/8" thick polycarbonate.

CONFORMANCE TO CODES & STANDARDS

The PXP Series meets or exceeds the following: UL 924, NEC requirements and NFPA 101.

DIMENSIONS

